

Mira Excel

Thermostatic Bath Shower Mixer



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

The Mira Excel Thermostatic BSM is the ultimate in reliability, providing the perfect solution for families with its thermostatic temperature control.

Product Information

Description	Colour	Product No.
Mira Excel BSM	Chrome	1.1598.001

Features & Benefits

Temperature control

Thermostatic temperature stability (shower & bathfill)

Easy to fit

Fits onto standard bath tap holes

Easy to service

Large, long-life filters and replaceable cartridge

For your customer

Separate flow and temperature controls

Automatic max temperature reduction when switching from bath to shower mode

Mira Cool Shield™ to ensure valve doesn't get hot during showering

Mira Magni-flo™ technology delivers up to 3x more flow, even at low pressure

4 spray 9cm showerhead with rub-clean nozzles



Product Specification

Tech Details

Temperature control

Control type: Thermostatic shower control & bath fill

Installation

Water entry points: Rising only

Inlet connections: 3/4" BSP Male

Outlet connections: 1/2" BSP Male

Reversed inlets supported: No = hot left, cold right only

Supply Conditions (hot and cold)

Cold water range: Up to 25°C

Hot water range: 50°C-85°C (operating)
55°C-65°C (recommended)

Minimum maintained pressure: 0.2 bar (2 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Performance

Flow rate (at handset): 14 l/min at 0.5 bar

Temperature stability: ± 2°C

Safety Features

Automatic shutdown: Shutdown within 2 secs (both bath and shower)

Factory set to safe max temp: Factory set to 46°C

Adjustable maximum temperature for on-site conditions

Dimensions

