

Mira Select Flex

Mixer Shower



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

Designed to provide the ultimate flexibility with large, easy to use levers and highly visible graphics for ultimate ease of use.

Product Information

| Description | Colour | Product No. |
|------------------|--------|-------------|
| Mira Select Flex | Chrome | 1.1679.001 |

Features & Benefits

Temperature control

Thermostatic temperature stability

Easy to fit

Quickly and easily fits onto reversed inlet inlet supplies

Easy to service

Large, long-life filters and replaceable cartridge

For your customer

Separate flow and temperature control levers for ease of use

Mira Magni-flow™ technology delivers up to 3x more flow, even at low pressure

Mira Cool Shield™ to ensure valve doesn't get hot during showering

Easy to glide shower head, extra long slide bar and hose

Slide bar can be corner mounted

Single spray Mira Everclear showerhead keeps limescale at bay

Designed in conjunction with the RNIB



Product Specification

Tech Details

Temperature control

Control type: Thermostatic

Installation

Water entry points: Rising, falling or rear

Inlet connections: 15 mm compression

Outlet connections: ½" BSP Male Flat Face or 15mm compression

Reversed inlets supported: Yes

Supply Conditions (hot and cold)

Cold water range: Up to 25°C

Hot water range: 50°C-85°C (operating)
55°C-65°C (recommended)

Minimum maintained pressure: 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Performance

Flow rate (at handset): 9 l/min at 0.5 bar

Temperature stability: ± 2°C

Safety Features

Automatic shutdown: Shutdown within 2 secs

Factory set to safe max temp: Factory set to 41°C

Approvals

KIWA UK approved product

WRAS approved

TMV2 Approved

TMV3 Approved

Water Efficient Product recommended



Dimensions

