
100093579 chrome

Concealed thermostatic 3/4" with wax thermostatic element. Built in non-return valve. Safety stop at 38°C . Flow rate 57,9 l/min. at 3 bar. It is required to order this item with at least one wall mounted stop valve.





Extension kit

| OPTION | SAP | FINISH | DIMENSION |
|--------|-----------|--------|-----------|
| 1 | 100185238 | CHROME | 30 mm |

Spare parts

| POS. | SAP | ART. | RRP* |
|------|-----------|--|------|
| 1 | 100103131 | MANETA SOFT TERMOSTATO CROMO | - |
| 2 | 100066742 | INSERTO PLASTICO MEZCLAD.TERMO.CLIP13X20 | - |
| 3 | 100046424 | ANILLO LIMIT.TEMP.TERM.BASIC | - |
| 4 | 100103125 | TRIM CARTRIDGE SOFT THERMOSTATIC | - |
| 5 | 100103128 | O-RING FRONT SOFT THERMOSTATIC | - |
| 6 | 100103133 | TRIM SOFT THERMOSTATIC | - |
| 7 | 100103129 | O-RING BACK SOFT | - |
| 8 | 100039544 | MONTURA REGULAD.TEMPERATURA FUTURE | - |
| 9 | 100060455 | FILTRO TERMOST. ENC. BASIC | - |

