

Prime Single Lever

Product code: AT2104 Product Finish: Matt Black EAN13 barcode: 5060344157643



Product features:


- · Metal construction throughout
- · Subtle soft sweeping design form
- Single lever control for effortless single handed control
- · Supplied compete with flexible tail pipes for fast simple fitting
- · Antisplash spout supplied as standard

Additional information / Parts included:

Includes triangular stabilising bracket, 1 x 2.0mm A/F Allen key, 1 x high flow aerator

Note: the image shown may not reflect the product finish, chrome finish is typically depicted

Product dimensions:



- Overall Height / projection: 254 mm
- Exit reach: 188 mm • Exit height: 159 mm Centre distance(s):
- Base diameter(s): 50 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 50 mm
- Spout diameter: 35 x 10 mm Spout aerator size: M24x1


Packaged properties:

Box length: 420mm Box depth: 75mm

Box width: 235mm Units per outer: 5

Tap only weight: 0.99kg Boxed weight: 1.65kg

Product flow characteristics:



- Min / Max water pressure: 0.3 (4.1L/M no NRV, 0.5 as STD) / 5.50 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G Mixed flow rate at 3 bar (litres / min): 13.61
- Control valve type: Single lever ceramic cartridge
- Product flow characteristics: Single flow
- Non return valve(s): Hot & cold (integral to tails)
- Aerator type: Dark blue honeycomb & hi-flow neostrahl
- · Accepts revolve / spray areator: Yes
- · Spout connection method: N/a
- Tail pipe inlet / outlet size: M10 / 1/2" BSP Male
- Inlet pipe type / length: flexible stainless braided hose / 365 mm

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners,
- Regular cleaning will prevent the build-up of lime scale and dirt After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives
- Warranty Summary (Full details available on request)
- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year