
# Astbury Monobloc C/W Integral Hendon Handspray

**Product Finish:** Forged Brass

AT3069 Product code:

EAN13 barcode: 5060344155205

## **Product features:**



- Quarter turn handle action for precise flow control
- Ceramic handle(s) as standard
- Integral diverter from spout to sprayhead (spout flow stops when spray activated)
- Leading design performance requiring higher pressures

# Additional information / Parts included:

The installation of this product should respect requirement IRN R090. Triangular stabiliser, Cache aerator key


Packaged properties:

Box length (mm): 605 Box depth (mm): 85 Box width (mm): 320

Units per outer: 5

Tap only weight (kg): 3.22 Boxed weight (kg): 3.96

### **Product dimensions:**



• Overall Height / projection (mm): 370

• Exit reach (mm): 229 Exit height (mm): 239 • Centre distance(s): N/A


• Base diameter(s) (mm): 60

Recommended hole diameter (mm): Ø 35

• Max. surface depth (mm): 50

• Spout diameter (mm): 20 • Spout aerator size: M20

#### **Product flow characteristics:**



- Min / Max water pressure (bar): 1.25 / 5.5
- Recommended / Max water temperature:  $46^{\circ}$ C /  $70^{\circ}$ C
- Part G Mixed flow rate at 3 bar (litres / min): 9.32
- Control valve type: Ceramic disc QT
- Product flow characteristics: Single flow
- Non-return/Check valve(s): Integral to H & C inlets and sprayhead
- Aerator type: Neoperl SLIM AIR CCSLC STD flow class V
- Accepts revolve / spray areator: No
- Spout connection method: Locking collar
- Tail pipe inlet / outlet size: 1/2" BSP Male / M10
- Inlet pipe type / length (mm): flexible stainless braided hose / 480

- Clean the product regularly using a mild washing up liquid, do not use any other cleaners.
  Regular cleaning will prevent the build up of lime scale and dirt
  After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request): Materials and workmanship defects warranted for 5 years .Valves and working parts warranted for 5 years Surface warranty defects warranted for 1 years .O-rings, hoses & gaskets warranted for 1 years

