PS BAS C

PISA Tap Range Pisa Basin Mixer With Clicker Waste Chrome



Features:

• Chrome plated to BS EN 248

Specification				
Style:	Contemporary			
Product Type:	Bathroom Tap			
Finish/Colour:	Chrome			
Main Construction Material:	Brass			
Mount Type:	Deck Mounted			
Handle Type:	Single Lever			
Connection Inlet:	M10x400mm x 1/2" BSP Flexible Tails			
Number of Tap Holes Required:	1			
Valve/Cartridge Type:	40mm Cartridge			
Plumbing System Suitability	All, Preferably Balanced			
Working Pressure Range:	Min. 0.2 bar, Max. 5.0 bar			
Maximum Hot Water Temperature: °c	65			
Maximum Dynamic Pressure: (bar)	5			
Maximum Static Pressure: (bar)	10			
Flow Type:	Single			
Flow Rate: (I/min @ 3 bar)	22.7			
Connection Outlet:	N/A			
Isolation Included:	No			

Dimensions (measurements in mm)

138

260

113

58

Product Certifications:

WRAS Certificate Number: 1707003 WRAS Expiry Date: 31/07/2022



Also available from the PISA Tap Range is:



⊔⊔ ⊥ 15 → ⊮			→	⊢ (j 1/4	"		
Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	1	2	3	5		
PS BAS C	5.1	8.6	12.6	18.3	22.7	29.5		

TECHNICAL DATA SHEET





Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Telephone: 0844 701 6274. Facsimile: 0844 701 6275. Web Site: www.bristan.com Email: enquire@bristan.com. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.

<35[∔]